

TECHNICAL DATA		Cone 500	Cone 900	Cone1300	Cone 1600
Tonnage	kN/US tons	180/20	220/24.5	440/49	440/49
Bending length, max.	mm	558	868	1300	1600
Distance between frames	mm	498	808	1230	1530
Throat	mm	200	200	200	200
Opening height, max	mm	400	400	400	400
Opening height, min.	mm	250	250	250	250
X-axis stroke	mm	400	400	400	400
X-axis speed	mm/s	375	375	375	200
X-axis repeating accuracy	mm	+/- 0.05	+/- 0.05	+/-0.05	+/- 0.05
Table height	mm	825	825	825	825
Y-axis bending stroke	mm	150	150	150	150
Y-axis repeating accuracy	mm	+/- 0.005	+/- 0.005	+/- 0.005	+/- 0.005
Y-axis bending speed	mm/s	10	10	10	10
Y-axis return speed	mm/s	100	100	100	100
R-axis stroke	mm	135	135	135	135
R-axis speed	mm/s	200	200	200	200
Motor power	kW	4,4	5	2x5.0	2x5.0
Machine weight	kg	1500	1800	2800	3000
Total width, (feet)	mm	815	1105	1525	1825
Toatal width, (frame)	mm	560	868	1300	1600
Total depth	mm	1198	1198	1198	1198
Total height,	mm	2100	2100	2100	2100
Control		Omron	Omron	Omron	Omron

